

SCL OILIFT REMOVER

Designed to remove heavy-duty oil stain & hydraulic oil spills on rough texture marble, granite and matte finished homogeneous tiles. Can also mix with SCL PPP Poultrice Powder to remove penetrated oil stain



PROCEDURE TO REMOVE ENGINE OIL , GREASE, INK STAIN, ETC USING SCL-OILIFT REMOVER

- Step 1: Wet the stone or tile surface with SCL-OILIFT solution.
- Step 2: Use a low speed polishing machine. Attached a black polishing pad to the drive plate. Begin the polishing. DO NOT allow the solution to dry on the surface. Apply the solution again if the grease has lightened. Repeat the polishing.
- Step 3: Now mix 180ml of SCL-STONECLEAN Xtra with a gallon of water into the solution tank. Rinse the entire floor with the diluted SCL-STONECLEAN Xtra. Change a new scrubbing pad when rinsing the floor with SCL-STONE CLEAN Xtra.
- Step 4: Leave the floor to dry for at least 12 hours. Apply SCL-STAIN X Penetrating Sealer or SCL-Clear Enhancer Sealer to give a brilliant color to the stone; especially a rough texture stone.

Important Note: Do not pick up SCL-OILIFT solution with a wet/dry vacuum at Step 2.
注意: 不可以應用吸水機將地面骯髒的溶劑漿拾起來。

